



DESIGN

HEIGHT	185mm nominal	
WIDTH	38mm	
LENGTHS	Custom up to 9.0m	

PROPERTIES

- ZINCALUME® steel alloy coated AZ150 conforms to AS1397
- COLORBOND® steel coated in accordance with AS2728 Category 3

Base Metal Thickness BMT (mm)	-	0.42
Tensile Strength (MPa)	-	550
Mass (kg/lineal mtr)	ZA CB	0.99 1.01
With Corestrip	ZA CB	No Yes

PERFORMANCE

Colerbond

- Quick fixing due to highest quality roll forming
- Straight, consistent and trouble-free performance
- Compatible with other gutter profiles from Pantex Roofing Systems

FASCIA 185

- FOR RESIDENTIAL AND INDUSTRIAL PROJECTS
- SUITABLE FOR METAL AND TILE ROOFING APPLICATIONS

QUALITIES

- ✓ High tensile steel supplied by Bluescope Steel.
- Available in all COLORBOND[®] steel colours and ZINCALUME[®] steel.

INSTALLATION

Maximum span between rafter brackets: 1200mm

- Use string line and level to align rafter brackets to achieve level fascia
- Secure rafter brackets to rafters with:
 8g x 20 Button Head, Needle point for timber
 10g x 16 Hex head, Self-drilling for metal
- Fit top of fascia over rafter brackets and clip it onto the bottom

Remove plastic coating from finished installation.

ACCESSORIES

- Rafter Bracket
- Joining Sleeve
- Internal Fascia Corner
- Internal Fascia Angle
- External Fascia Corner
- Barge Mitres

Next Day Delivery

3E003.05

www.pantexroofing.com.au (07) 3897 8200 | mail@pantexroofing.com.au