



HEIGHT	143mm		
WIDTH	125mm		
LENGTHS	Custom up to 9.0m		
EFFECTIVE CROSS SECTIONAL AREA	Slotted	7753 mm ²	
	Unslotted*	9881 mm²	
*Utilising Rear Overflow Space	cers		

PROPERTIES

- ZINCALUME® steel alloy coated AZ150 conforms to AS1397
- COLORBOND® steel coated in accordance with AS2728 - Category 3

Base Metal Thickness BMT (mm)	-	0.42
Tensile Strength (MPa)	-	550
Mass (kg/lineal mtr)	ZA CB	1.20 1.22
With Corestrip	ZA CB	No Yes

QUALITIES

- Large capacity high front gutter ideal for hiding the ends of roof tiles and sheeting.
- Available slotted or unslotted
- Matching Squareline 140 Barge Capping profile available

MIGHTY M **SQUARELINE** 140

- FOR RESIDENTIAL, INDUSTRAL AND **COMMERCIAL PROJECTS**
- RESIDENTIAL HOUSING IN HIGH RAINFALL REGIONS
- ✓ Available in all COLORBOND® steel colours and ZINCALUME® steel

Allow for gutter "fall" of at least 1 in 500 from the

INSTALLATION

designated high points Mighty M Squareline 140 Gutter can be fixed to Pantex Metal Fascia 185 with spring clips, **PANTEX FASCIA** overstraps and overflow spacers*. 185: Should be spaced every 900mm maximum. Use internal gutter brackets **OTHER FASCIA** spaced at 900mm for metal or

timber fascia Remove plastic coating from finished installation.

ACCESSORIES

- Spring Clips
- Overstraps
- Internal Gutter Brackets
 5mm Overflow Spacers
- Stop Ends
- Internal Corners
- External Corners

Next Day Delivery



^{*}Refer to Gutter Overflow & Drainage Guidelines for overflow spacer requirements.