



## MINI CORRUGATED SHEETING

- FOR A WIDE RANGE OF WALL CLADDING APPLICATIONS
- HORIZONTAL OR VERTICAL INSTALLATION

### DESIGN

RIB HEIGHT	6mm
WIDTH COVERAGE	820mm
MAXIMUM LENGTH	6.0m

### SPANS

Base Metal Thickness BMT (mm)		0.42	0.48
WALLS	Single Span (mm)	1200	1200
	End Span (mm)	1000	1000
	Internal Span	1000	1000
	Overhang	900	900

### FASTENERS

- All fasteners must conform to AS3566 – Class 3.
- Valley fix at 7 locations per sheet (every 5th valley).
- Sheet overlap may require stitching using pop rivets.

	TIMBER	STEEL	STEEL (Internal only)
Walling	Self Drilling M5.4 x 28mm Mini Hex Concave Head		Pop Rivets 3.2mm

### QUALITIES

- ✓ Classic Australian profile with soft curves and flowing lines
- ✓ Suitable for interior and exterior walling applications
- ✓ Ease of handling and installation
- ✓ Available in all COLORBOND® steel colours and ZINCALUME® steel

### PROPERTIES

- Next Generation ZINCALUME® steel alloy coated AM125 conforms to AS1397:2011
- COLORBOND® steel in accordance with AS2728:2013 AM100 (100g/m<sup>2</sup>)

Base Metal Thickness BMT (mm)		0.42	0.48
Tensile Strength (Mpa)		550	550
Total Coated Thickness (mm)	ZA	0.47	0.53
	CB	0.47	0.53
Mass (kg/m <sup>2</sup> )	ZA	3.95	4.02
	CB	4.02	4.58
Mass (kg/lm)	ZA	3.26	3.70
	CB	3.32	3.78