



## MIGHTY M SQUARELINE 140 UNSLOTTED

### DESIGN

HEIGHT	143mm	
WIDTH	125mm	
LENGTHS	Custom up to 9.0m	
EFFECTIVE CROSS SECTIONAL AREA	Slotted	7753 mm <sup>2</sup>
	Unslotted*	9881 mm <sup>2</sup>
*Utilising Rear Overflow Spacers		

### PROPERTIES

<ul style="list-style-type: none"> <li>ZINCALUME® steel alloy coated AZ150 conforms to AS1397</li> <li>COLORBOND® steel coated in accordance with AS2728 – Category 3</li> </ul>		
Base Metal Thickness BMT (mm)	-	0.42
Tensile Strength (MPa)	-	550
Mass (kg/lineal mtr)	ZA	1.20
	CB	1.22
With Corestrip	ZA	No
	CB	Yes

### QUALITIES

- ✓ Large capacity high front gutter ideal for hiding the ends of roof tiles and sheeting.
- ✓ Available slotted or unslotted
- ✓ Matching Squareline 140 Barge Capping profile available

- FOR RESIDENTIAL, INDUSTRIAL AND COMMERCIAL PROJECTS
- RESIDENTIAL HOUSING IN HIGH RAINFALL REGIONS

✓ Available in all COLORBOND® steel colours and ZINCALUME® steel

### INSTALLATION

Allow for gutter “fall” of at least 1 in 500 from the designated high points

<b>PANTEX FASCIA 185:</b>	Mighty M Squareline 140 Gutter can be fixed to Pantex Metal Fascia 185 with spring clips, overstraps and overflow spacers*. Should be spaced every 900mm maximum.
<b>OTHER FASCIA</b>	Use internal gutter brackets spaced at 900mm for metal or timber fascia

Remove plastic coating from finished installation.

\*Refer to Gutter Overflow & Drainage Guidelines for overflow spacer requirements.

### ACCESSORIES

- Spring Clips
- Internal Gutter Brackets
- Stop Ends
- External Corners
- Overstraps
- 5mm Overflow Spacers
- Internal Corners