



## DESIGN

GIRTH	100mm - 1200mm
MINIMUM LENGTH	0.5m
MAXIMUM LENGTH	8.0m
MINIMUM FOLD DIMENSION	10mm

## PROPERTIES

✓ ZINCALUME® steel alloy coated AZ150 conforms to AS1397		
✓ COLORBOND® steel coated in accordance with AS2728 – Category 3		
Base Metal Thickness BMT (mm)	0.40	0.55
Tensile Strength (MPa)	300	300
With Corestrip	ZA CB	No Yes

## QUALITIES

- ✓ Economical; Stylish; Strong; Durable; Versatile
- ✓ Available in all COLORBOND® steel colours and ZINCALUME® steel

# CUSTOM FLASHINGS

- FOR RESIDENTIAL AND COMMERCIAL APPLICATIONS

## FLASHING SELECTION GUIDE

View our Flashing Selection Guide for commonly used flashing profiles and details.

## HOW TO ORDER

1. Choose your preferred profile type, material and finish.
2. If using COLORBOND® steel, nominate the side on which the colour is required.
3. Specify dimension by letters shown in the diagrams. A larger image can be viewed on our website.
4. Nominate the angles on all bends.
5. Nominate the quantity and length of the flashing.

### Example

1. Type 4, Colour Surfmist
2. Colour on Side C
3. A - 15mm, B - 100mm, C - 150mm, D - 150mm
4. AB - 65°, BC - 90°, CD - 90°
5. 1 of, 2550mm

<b>Type 1</b> 	<b>Type 2</b> 	<b>Type 3</b> 	<b>Type 4</b> 	<b>Type 5</b> 	<b>Type 6</b> 
<b>Type 7</b> 	<b>Type 8</b> 	<b>Type 9</b> 	<b>Type 10</b> 	<b>Type 11</b> 	<b>Type 12</b> 
<b>Type 13</b> 	<b>Type 14</b> 	<b>Type 15</b> 	<b>Type 16</b> 	<b>Type 17</b> 	<b>Type 18</b> 
<b>Type 19</b> 	<b>Type 20</b> 	<b>Type 21</b> 	<b>Type 22</b> 	<b>Type 23</b> 	<b>Type 24</b> 
<b>Type 25</b> 	<b>Type 26</b> 	<b>Type 27</b> 	<b>Type 28</b> 	<b>Type 29</b> 	<b>Type 30</b> 
<b>Type 31</b> 	<b>Type 32</b> 	<b>Type 33</b> 	<b>Type 34</b> 	<b>Type 35</b> 	<b>SPECIAL</b> 